

Smart Positioner YT-2700 series (compact size)

Product Number: YT-2700 S n 1 (specify your requirement)


Model	Motion Type	Acting Type	Explosion Proof	Lever Type					Connection Type	Communication	Option	Fail Option
				Linear	Rotary		Rotary					
YT-2700	L Linear	S Single	n Non-Explosion	1 10~40mm	1 M6 × 34L		1 PT	0 NONE	0 NONE	F Fail Freeze		
				2 20~70mm	2 M6 × 63L		2 NPT					
	R Rotary	i Ex ia IIC T6/T5	3 50~100mm	3 M8 × 34L		2 + HART	1 + PTM	S Fail Safe				
			4 100~150mm	4 M8 × 63L								
				5 NAMUR								



YT-2700



compact size



Item · Type	YT-2700L	YT-2700R
Input Signal	4~20mA DC	
Supply Pressure	1.4 ~ 7kgf /cm ² (0.14 ~ 0.7MPa)	
Stroke	10~150mm	0 ~ 90°
Impedance	Max.460Ω / 20mA DC	
Air Connection	PT(NPT)1/4	
Gauge Connection	PT(NPT)1/8	
Conduit	PF1/2 (G1/2)	
Repeatability	±0.3% F.S.	
Ambient Temp.	Operating Temp.	-30°C ~ 85°C (-22~185° F)
	Explosion Temp.	-40~60°C (T5)/-40~40°C (T6)
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Air Consumption	0.01LPM(sup=1.4k)	
Flow Capacity	22LPM	
Output Characteristics	Linear, EQ%, Quick Open user set (16 Point)	
Material	Aluminum Diecasting	
Protection	IP66	
Explosion Proof type	Ex ia IIC T6/T5	
Weight	0.82kg(1.8lb)	

YT-2700 Compact smart valve positioner accurately controls valve stroke, according to input signal of 4-20mA being delivered from controller.

- Fail freeze function
- Near zero air consumption level
- HART communication
- Fail safe function
- PD control
- 4 buttons for local control
- LCD display
- Feedback signal
- Auto calibration
- Single acting only